

# Standard ///Band saw Bench



The Williams and White
Standard Bandsaw Bench
is designed to be a universal
bandsaw maintenance station.
This bench provides all the
necessary features to maintain
your bandsaws in a heavy duty
package.



## **Highlights**

Square beam design for durability and stability

Will fit all stretcher brands \_\_\_\_\_\_\_ versitility for all environments


Mild steel or NiChrome precision ground for hammering (both sides) anvils available

Manual extendable saw length adjustment — to fit multiple lengths of saws

Manual saw lift for saw inspection


# Williams and White Dish-O-Matic II System

- Patented Williams & White Dish-O-Matic II Stretcher Roll allows the operator to tension and level the blade in one setup
- <u>Drastically reduces the amount of hammering required</u>
- Reduces the need to flip the saw




## Extendable saw turn around

<u>UHMW turn around tracks can</u> <u>extend and contract for varying</u> saw lengths



#### **Hardened alignment bolts**

Both top and bottom of saw for stability as the saw tracks through the rolls




### **Options**

#### **UHMW** air inspection lift

- Lifts the saw while in place on the bench to efficiently inspect band saw blade tension
- Hydraulic roll pressure
- + Large anvil upgrade
- **⊢** Variable speed rolls
- **H** Additional floor tracks

#### Band saw welding clamp

- Hardened and ground hammering anvil
- Optional heating element
- Spring retraction
- 10", 12", 16" capacity
- Pneumatic clamping



# Available Nichrome leveling slabs

NiChrome slabs are extremely durable and wear resistant and offer a longer life span than traditional steel slabs.



## **Specifications**

Wheel diameter
Leveling slabs
Stretcher roll
Saw length
Saws
Electricity

(2) 36 Inches
(2) 36" x 8" x 4" mild steel
Dish-O-Matic 10D
21' x 5"
Single cut
480Vac,3ph, 60hz

(2)914mm
(2) 914mm x 203mm x102mm mild steel
Dish-O-Matic 10D
6400mm x 127mm
Single cut
480Vac,3ph, 60hz
•